

# PROTECT 800

## SPECIFICATIONS



*Designed for continuous air dis-infection and odour control in medium indoor spaces, the Novaerus Protect 800 uses patented filter-free ultra-low energy plasma technology with a 2-speed fan.*



### MODEL

NV800

Placed on a stand or wall mounted

Supplied with 2m power cord

### ELECTRICAL RATING

230 VAC, 50 Hz, 20 W

Fuse Rated at 250 VAC, 3 Amps, Listed

### POWER CONSUMPTION

20 W

### CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

### DIMENSIONS + WEIGHT

36.6 cm(h) x 36.5 cm(w) x 11.4 cm(d)

4.7kg

### ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord

### FAN AIR FLOW VOLUME

Speed I = 220 m<sup>3</sup>/hr

Speed II = 260 m<sup>3</sup>/hr

### NOISE LEVEL

Speed I = 40 dB

Speed II = 45 dB

### OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity, 2000m

### SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

### QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001

Conforms to the Medical Device Directive