

# PROTECT 200

## SPECIFICATIONS



*Designed for continuous air dis-infection and odour control in small indoor spaces, the Novaerus Protect 200 uses patented filter-free ultra-low energy plasma technology with a single speed fan.*



### MODEL

NV200

Wall mountable, countertop, or stand-alone  
Supplied with 2m power cord

### ELECTRICAL RATING

230 VAC, 50 Hz Single Phase, 20 W  
Fuse rated at 250 VAC, 3 Amps, Listed

### POWER CONSUMPTION

20 W

### CONSTRUCTION + COLOR

Precision cut fabricated metal casing in a white anti-bacterial powder coat finish.

### DIMENSIONS + WEIGHT

28.3 (h) x 13.2 (w) x 10.8 (d) cm  
3.4kg

### ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord.

### FAN AIR FLOW VOLUME

85 m<sup>3</sup>/hr

### NOISE LEVEL

35 dB

### OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity, 2000m

### SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

### QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001