



# NV800

## SPECIFICATIONS



*NOVAERUS uses patented active purification technology to continuously pull contaminated indoor air across internal short-exposure plasma coils, deactivating airborne microorganisms and viruses at the DNA level*

### MODEL

NOVAERUS NV800

Stand or Wall mounted supplied with 2m power cord

### ELECTRICAL RATING

230 VAC, 50 Hz, 20 W

Fuse Rated at 250 VAC, 3 Amps, Listed  
Power consumption maximum 20 Watts

### CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

### DIMENSIONS + WEIGHT

36.6 cm(h) x 36.5 cm(w) x 11.4 cm(d)

4.7kg

### ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord

### FAN AIR FLOW VOLUME

Speed I = 220 m<sup>3</sup>/hr

Speed II = 260 m<sup>3</sup>/hr

### NOISE LEVEL

Speed I = 40 dB

Speed II = 45 dB

### OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity, 2000m

### SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

### QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001.

CONFORMS to the Medical Device Directive

35 Melrose Place | Stamford | CT 06902 | EE. UU. - T: +1 866 508 1118

DCU Alpha Innovation Campus | Old Finglas Road | Glasnevin |

Dublin 11 | Ireland - T: +353 1 907 2750

[www.novaerus.com](http://www.novaerus.com)