

Protect 200

Powered by
NanoStrike[®]
technology



Designed for continuous air dis-infection and odour control in small indoor spaces, the Novaerus Protect 200 uses one NanoStrike[®] plasma coil with a single speed fan. Can be wall-mounted or placed on any surface and plugs into any outlet.

MODEL

Protect 200
Wall mountable or countertop unit supplied with 2m power cord

DCU Alpha | Old Finglas Road | Glasnevin
Dublin 11 | D11 KXN4 | Ireland
T: +353 1 907 2750 | www.novaerus.com

SPECIFICATIONS

ELECTRICAL RATING

Single Phase, 220-240 VAC, 50-60 Hz,
Fuse rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION

Maximum 19W

CONSTRUCTION + COLOUR

Precision cut fabricated metal casing in a white anti-bacterial powder coat finish.

DIMENSIONS + WEIGHT

28.3 cm (h) x 13.2 cm (w) x 10.8 cm (d)
3.4kg

ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord.

FAN AIR FLOW VOLUME

80 m³/hr

NOISE LEVEL

35 dB

OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity

SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001

IEC 61010

IEC 60601-1-2, Fourth Edition

CE Mark

