

Protect 800

Powered by
NanoStrike[®]
technology



Designed for continuous air dis-infection and odour control in medium indoor spaces, the Novaerus Protect 800 (NV800) uses two NanoStrike[®] plasma coils with a 2-speed fan. Can be wall-mounted or placed on a stand and plugs into any outlet.

MODEL

NV800

Wall mountable, countertop with table stand or mounted on portable high tower stand, supplied with 2m power cord

SPECIFICATIONS

ELECTRICAL RATING

Single Phase, 220-240 VAC, 50-60 Hz
Fuse Rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION

Maximum 14W

CONSTRUCTION + COLOUR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

DIMENSIONS + WEIGHT

36.6 cm (h) × 36.5 cm (w) × 11.4 cm (d)
4.7kg

ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord

FAN AIR FLOW VOLUME

Speed I = 220 m³/hr
Speed II = 260 m³/hr

NOISE LEVEL

Speed I = 40 dB
Speed II = 45 dB

OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity

SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001.

Conforms to the Medical Device Directive (MDD) 93/42/EEU

IEC 60601-1, Third Edition

IEC 60601-1-2, Fourth Edition

CE Mark

