



PROTECT 200

SPECIFICATIONS



Designed for continuous air disinfection and odor control in small indoor spaces, the Novaerus Protect 200 uses patented filter-free ultra-low energy plasma technology with a single speed fan.



MODEL

NV200

Wall mountable, countertop or stand-alone
Supplied with 8.2 ft power cord

ELECTRICAL RATING

120VAC, 60Hz, 0.08A

Fuse rated at 125VAC, 3 amps, Listed

POWER CONSUMPTION

20 watts

CONSTRUCTION + COLOR

Precision-cut fabricated metal casing with an off-white, powder coat finish

DIMENSIONS + WEIGHT

5.2" w x 11.1" h x 4.3" d

7.6 lbs.

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded 3 pin power cord

FAN AIR FLOW VOLUME

50 ft³/min

OPERATING CONDITIONS

10-35°C, 10-75% Relative Humidity, 2000m

SHIPPING / STORAGE CONDITIONS

5°C-50°C, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 and OHSAS 18001

7525 SE 24th Street | Suite 510 | Mercer Island | WA 98040 | USA
T: 1.866.508.1118 | www.novaerus.com

Document No. 610-00-0158 Rev G.
COPYRIGHT © 2018 NOVAERUS US, INC.